



优洛斯胶带

Adhesive Tapes

粘性胶带

泡棉保护胶带

Sicad Group

The adhesive tape experience

司克集团



优洛斯胶带

分享粘性胶带的经验
the adhesive tape experience

Industry /

SF 7200 TIP TAPE

Standard protection foam, high adhesion 高粘着力，保护泡棉胶带

Protection foam developed for the automotive industry. Good adhesion on difficult surfaces. Acts as a double protection, during manufacturing (against dust), but also during transport (against shocks). 保护泡棉胶带，适合汽车行业用。据有高服帖性，可在生产过，运输程中保护表面刮伤。

Adhesive 胶水 : Acrylic water based 亚克力水性胶

Backing 基材 : Laminated foam 泡棉 + PE 膜

Applications 用途 : Temporary protection 暂时保护用

MAIN FEATURES



●●●●○
Conformability 4



Protection



Removable

TECHNICAL DATA

Adhesion 粘着力 4.5 N/25mm

Elongation to break 伸长率 70 %

Temperature resistance 耐温 60 °C

Tensile strength 抗张力 50 N/25mm

Total thickness 总厚度 0.8 mm



优洛斯胶带

分享粘性胶带的经验
the adhesive tape experience

Industry /

SF 7210 TIP TAPE

Standard protection foam, medium adhesion 中粘着力，保护泡棉胶带

Ideal to protect glass, varnished wood, plastics, ceramics, etc. in the furniture industry, ship building and glass manufacturing. Acts as a double protection, during manufacturing (against dust), but also during transport (against shocks). 适合保护玻璃，木头，塑胶，陶瓷表面等。家装，造船，玻璃生产中，运输中都可应用到

Adhesive 胶水 : Acrylic water based 亚克力水性胶

Backing 基材 : Laminated foam 泡棉 + PE 膜

Applications 用途 : Temporary protection 暂时保护用

MAIN FEATURES



●●●●○
Conformability 4



Protection



Removable

TECHNICAL DATA

Adhesion 粘着力 3 N/25mm

Elongation to break 伸长率 70 %

Temperature resistance 耐温 60 °C

Tensile strength 抗张力 50 N/25mm

Total thickness 总厚度 0.8 mm



优洛斯胶带

分享粘性胶带的经验
the adhesive tape experience

Industry /

SF 7211 TIP TAPE

Standard protection foam, low adhesion 低粘着力，保护泡棉胶带

Protection for delicate surfaces: metal, bicomponent paints, precious wood. Acts as a double protection, during manufacturing (against dust), but also during transport (against shocks)。可保不同的表面。例如铁面，漆，木，等。适合在生产，运输过程中用。

Adhesive 胶水 : Acrylic water based 亚克力水性胶

Backing 基材 : Laminated foam 泡棉 + PE 膜

Applications 用途 : Temporary protection 暂时保护用

MAIN FEATURES



●●●●○
Conformability 4



Protection



Removable

TECHNICAL DATA

Adhesion 粘着力 1 N/25mm

Elongation to break 伸长率 70 %

Temperature resistance 耐温 60 °C

Tensile strength 抗张力 50 N/25mm

Total thickness 总厚度 0.8 mm



优洛斯胶带

分享粘性胶带的经验
the adhesive tape experience

Industry /

SF 7220 TIP TAPE

Thicker protection foam, medium adhesion 中粘着力，厚的保护泡棉胶带

High protection of glass, varnished wood, plastics, ceramics in the furniture industry, ship building and glass manufacturing areas. Acts as a double protection, during manufacturing (against dust), but also during transport (against shocks). 适合保护玻璃，木头，塑胶，陶瓷表面等。家装，造船，玻璃生产中，运输中都可应用到

Adhesive 胶水 : Acrylic water based 亚克力水性胶

Backing 基材 : Laminated foam 泡棉 + PE 膜

Applications 用途 : Temporary protection 暂时保护用

MAIN FEATURES



●●●●○
Conformability 4



Protection



Removable

TECHNICAL DATA

Adhesion 粘着力 3 N/25mm

Elongation to break 伸长率 75 %

Temperature resistance 耐温 60 °C

Tensile strength 抗张力 55 N/25mm

Total thickness 总厚度 1.6 mm



优洛斯胶带

分享粘性胶带的经验
the adhesive tape experience

Industry /

SF 7221 TIP TAPE

Thicker protection foam, low adhesion 低粘着力，厚的保护泡棉胶带

Maximum protection for delicate surfaces: metal, bicomponent paints, precious wood. Acts as a double protection, during manufacturing (against dust), but also during transport (against shocks). 适合保护玻璃，木头，塑胶，陶瓷表面等。家装，造船，玻璃生产中，运输中都可应用到

Adhesive 胶水 : Acrylic water based 亚克力水性胶

Backing 基材 : Laminated foam 泡棉 + PE 膜

Applications 用途 : Temporary protection 暂时保护用

MAIN FEATURES



●●●●○
Conformability 4



Protection



Removable

TECHNICAL DATA

Adhesion 粘着力 1 N/25mm

Elongation to break 伸长率 75 %

Temperature resistance 耐温 60 °C

Tensile strength 抗张力 55 N/25mm

Total thickness 总厚度 1.6 mm



优洛斯胶带

分享粘性胶带的经验
the adhesive tape experience

Industry /

SF 7222 TIP TAPE

Thicker protection foam, high adhesion 高粘着力，厚的保护泡棉胶带

High protection of glass, varnished wood, plastics, ceramics with high adhesion level for the furniture industry, ship building and glass manufacturing areas. Acts as a double protection, during manufacturing (against dust), but also during transport (against shocks). 适合保护玻璃，木头，塑胶，陶瓷表面等。家装，造船，玻璃生产中，运输中都可应用到

Adhesive 胶水 : Acrylic water based 亚克力水性胶

Backing 基材 : Laminated foam 泡棉 + PE 膜

Applications 用途 : Temporary protection 暂时保护用

MAIN FEATURES



●●●●○
Conformability 4



Protection



Removable

TECHNICAL DATA

Adhesion 粘着力 4.5 N/25mm

Elongation to break 伸长率 75 %

Temperature resistance 耐温 60 °C

Tensile strength 抗张力 55 N/25mm

Total thickness 总厚度 1.6 mm